

Model No.: 192-6636 Polished Chrome



8" Gooseneck Kitchen Faucet With Wrist Blade Handles




Helpful Information

Helpful Tools

Tools:

Gather the necessary tools as shown below to complete the installation of this faucet. Some may not be needed depending on the model of faucet you are installing.





LIMITED LIFETIME WARRANTY

Compass Manufacturing International warrants to the original consumer purchaser that the faucet be free from defects in material and workmanship for as long as the original consumer purchaser owns the home in which the faucet was first installed.

In the event that Freendo faucets are used in a Commercial Application, this warranty is limited for a period of 5 years, unless otherwise specifically stated in the catalog and/or price book.

Compass Manufacturing International will replace, free of charge, during the applicable warranty period, any part or finish that proves defective in material and/or workmanship under normal installation, use and service. This warranty shall not apply to goods which have been subject to accidents, negligence or improper installation. Compass Manufacturing International will not be liable for other damages or losses, including, but not limited to: labor charges and/or damages incurred in installation, repair or replacement as well as any other kind of loss or damage. Proof of purchase from the original consumer purchaser must be made available for all warranty claims.

Compass Manufacturing International recommends using a professional plumber for all installation and repair. Compass Manufacturing International will, at its discretion, provide new or equivalent replacement parts for any product that proves to be defective under normal usage and service. Replacement parts may be obtained by emailing the address below, calling the number below or by writing to:


Compass Manufacturing International

Freendo Product Service 6702 Enterprise Drive Louisville, KY 40214 800.626.3525 warranty@cmiproduct.com


Revised 3/22/18

800.626.3525

Preparation / Mounting




- 1. Shut off water supply and drain lines. Clean sink surface thoroughly. Make sure mounting area is clean and dry.
- 2. Remove the locknut 16 and washer 15 from faucet. Don't remove the putty plate 14 from faucet.




3. Position the faucet on the countertop with putty plate 14. Replace the washer 15 and the locknut 16 on the faucet, tighten the locknut (18) by hand.

Configuration




Connect to water supply lines with either:

- (A) 3/8" O.D.Copper tubing (ball nose risers with the coupling nuts or;
- (B) 3/8" Copper tubing (no ball) with supplied tube head interior connector or;
- (C) IPS faucet connectors (1/2")



Important:

Tighten connection with two wrenches to prevent damage to tube body. Be careful not to bend the stem as this will void the product warranty.



Important:

Remove the aerator and let both hot and cold water run for one minute. This will help clean any debris that might clog the system. Re-assemble aerator.

Test system for leaks.

3

Parts Diagram / List

