







## Westdale - Single Handle Tub & Shower Faucet







- \* Pressure Balanced Premium Ceramic Cartridge (Type F)
- \* Solid Brass Waterway Construction with 1/2"-14 NPT Connection
- \* Back to Back Installation Option
- \* Integral Stops, Diverter Tub Spout
- \* 4-3/4" 10 Function Showerhead
- \* Stainless Steel Shower Arm
- \* Stainless Steel Plate
- \* Zinc Die Cast Tub Spout
- \* Showerhead Flow Rate: 1.5 GPM (5.7 L/MIN) MAX @ 80PSI -Meets EPA WaterSense\*
- \* Tub Spout Flow Rate: 6.5 GPM (24.7 L/MIN) MAX @ 80PSI
- \* 100% Pressure System Tested
- \* Lifetime Limited Warranty; 5 year Warranty from Date of Purchase for Commercial Use

Project / Job Name	
Architect / Engineer	
Contractor	
Model	
Quantity	

## Model No.: 192-8101 (MB) 192-8100 (BN) 192-8102 (BS) 192-8099 (CH) **Showerhead Functions:** Rinse Pressure Massage Rainfall ||||||IIIIII ||||||6-11/16"(170mm) Turbo Combination Pressure Turbo Pressure Cartridge (Type F) Model : 892-6159 Aerated Pause Massage **Product Compliance:** - ASME A112.18.1 / CSA B125.1 - ANSI A117.1 (ADA)

Compass Manufacturing International LLC

• ASSE 1016